



Product range



This is a standard high performance valve for on-off and control in both wet and dry processes. Extremely reliable shutoff performance have made it popular amongst users worldwide for decades. The modular design and simple maintenance makes it also easy to achieve low cost of ownership.



This is an isolation valve for tanks which require a short face-to-face. With origin in the MV valve, the TV features a unique flange drilling pattern and actuator which enable direct assembly on the tank. Any transmitters can be dismounted without draining the tank.



WB, WB11, WB12 and WB14

This performance range seal tight independent of pressure direction and features valve body bores with no pockets where the media can collect. This makes them ideal for water treatment and biomass installations among many others.



This is a resilient seated high performance shut-off valve with superior flow characteristics, offering bi-directional zero leakage shut-off. The fully lugged body design makes it also suitable for deadend services.



The retainer ring sealing system on both

ΧV

sides of the gate assure perfect gate guidance, high resistance to pressure peeks and a bi-directional tight shut-off. XV is supplied with either a fully or a semi lugged valve body.



Junk Trap JT

This product is designed for cleaners to minimize turbulence, erosive wear and build-up of solids and reject material. It is supplied with RKO on top, the square JTV in the bottom and the reject tank in between the two valves.



SLV and **SLF**

These push through slurry valves are recommended for highly abrasive and demanding slurry. SLV is the compact lugged high performance version while SLF is the wide body fully flanged heavy duty version.



RKO

This is a roboust valve for high density cleaners containing large amount of abrasive and difficult solids. A straight bevel gate edge cut through and provide a tight seal against the seat while the larger square outlet enable full release of difficult media at drain sequence.



HL, HG, HP and HPT

Stafsjö's knife gate valves with throughgoing gates are known for their superior flow characteristics and reliable bi-directional zero leakage shut-off on highly concentrated media and static media columns. They are ideal pulp tower isolation valves, available in several pressure ratings and materials making it easy to customize to different process conditions.



SLH and SLX

Our most extreme slurry valves for high pressure tailing systems that requires 20 up to 50 bar pressure rated valves.



D₂G

The D2G have two hard chromed gates working towards each other in the bore providing extremely fast operation. It is suitable for stock preparation and wood chip cleaners or as junk traps in recycled



RKS

This is a welded isolating valve for wet or dry low pressure systems with sludge, powder or granulate. Sizes ranges from 200 mm up to 1000 mm, with either a square or rectangular bore.



HX

With origin in Stafsjö's HP range this is an all-over reinforced version capable of handling the most demanding high pressure applications. It is supplied in stainless steel as standard but SMO 254 and Titanium versions are also available for chlorine and bleaching stage in pulp related processes.















Offshore





Water treatment









About Stafsjö

Many major players in within pulp and paper, mining, steel, power, offshore, chemical, water treatment, biomass, food and beverage depend on our knife gate valves reliability and performance every minute, every day year after year. Some of the valves have been in operation for decades and still perform when required.

We manufactured our first valve in 1881. Decades of experience and co-operation with customers combined with our strong focus on quality, production efficiency and valve development, have resulted in a wide range of knife gate valves characterised by innovation, reliability and high performance.

Through our sister company Ebro Armaturen and external sales partners across the world we are able to provide fast deliveries, high quality service and support to local markets worldwide.

Further information is available on www.stafsjo.com.

Stafsjö Valves AB SE-618 95 Stavsjö, Sweden

+46 11 39 31 00 | info@stafsjo.se www.stafsjo.com

A Bröer Group company www.broer-group.com

